

## DSM 400 – Powerful floor grinder for substrate preparation and renovation

Equipped with our powerful diamond tools, the DSM 400 is ideal for smoothing uneven floors and preparing the substrate up to areas of 500 sqm. With the decoating diamonds, it effectively removes adhesives, fillers and coatings on concrete or concrete screed.



### Applications

Grinding screeds, screed, asphalt, remove adhesives, coatings, fillers, regulate uneven floors



Compact switch with integrated overload protection



ETX-Easy Tool Exchange

Technical data		Equipment variants	
Ref. No.		72800	728001
Voltage	V	400	230
Frequency	Hz	50	50
Power output	kW	4	2.2
Working width	mm	400	400
No. of tools	mm	1 x 400	1 x 400
Grinding pressure floor	kg	30.5 - 53	30.5 - 53
Operating weight	kg	102	74.5
Edge distance	mm	10	10
Tool speed	r.p.m.	900	600
Ø-Dust control	mm	50	50
Dimensions LxWxH	cm	65 x 45 x 75	65 x 45 x 75
Tool mount		ETX1	ETX1

Special characteristics
ETX – Easy tool exchange
Diamond floating device
Ergonomical handle design
Motor overload protection
Grinding pressure, adjustable
Transport grip
Dead man switch
Suction ring with height adjustment

DSM 400 Accessories and tools, Grinding from page 33