

Technical data		
Ref. No.		617000
Voltage	V	230
Frequency	Hz	50/60
Power input	kW	1.2
Operating weight	kg	42
Dimensions L x W x H	cm	73 x 41 x 130
Noise level	dB(A)	78
Suction hose, antistatic	m	5
Ø – Suction outlet	mm	38
Underpressure	kPa	23
Volume flow	m³/h	170
Filter cleaning		manually
Filter class		HEPA 13

STS 130 – Industrial vacuum for the construction industry with effective filter cleaning, H-certified

The STS 130 model is equipped with a pre-filter and HEPA filter as standard. Filter cleaning through air pulse process. With 3-stage dust filtration: 1st stage for coarse dust, 2nd stage with 99.9 % via a polyester pre-filter, 3rd stage via 2x HEPA filters with 99.995 %. Dust is collected in a transparent and easily transportable plastic bag (Dustbag). Including hand tube with floor suction nozzle and rubber strip, brush strip, hose (length 5 m, hose connection \emptyset 38 mm, antistatic), Dustbag and cable ties.



Standard with cable tie holder



Large abrasion-resistant transportation wheels

Special characteristics

Robust in design Dust separation in Dustbag Large abrasion-resistant transportation wheels Certified according to dust class H Antistatic hoses

