



## STS 260 – Robust industrial vacuum with H-certification

The STS 260 is ideal for construction, concrete, grinding and plaster dust. The vacuum unit is equipped as standard with a pre-filter and HEPA filter as well as a click system for attaching the suction hose. Filter cleaning through air pulse process. With 3-stage dust filtration: 1st stage for coarse dust, 2nd stage with 99.9 % via a polyester pre-filter, 3rd stage via 2x HEPA filters with 99.995%. Dust is collected in a transparent and easily transportable plastic bag (Dustbag). Including hand tube with floor suction nozzle and rubber strip, brush strip, hose (length 5 / 10 m, hose connection Ø 50 mm, anti-static), Dustbag and cable ties.



With click system for suction hose attachment



Dust separation in Dustbag

### Technical data

Ref. No.	617001	
Voltage	V	230
Frequency	Hz	50/60
Power input	kW	2.2
Operating weight	kg	55
Dimensions L x W x H	cm	73 x 48 x 138
Noise level	dB(A)	78
Suction hose, antistatic	m	5
Ø – Suction outlet	mm	50
Underpressure	kPa	23
Volume flow	m <sup>3</sup> /h	340
Filter cleaning	manually	
Filter class	HEPA 14	

### Special characteristics

- Robust design
- Dust separation in Dustbag
- Large abrasion-resistant transportation wheels
- Certified according to dust class H
- Antistatic hoses

